

## Component Video with Stereo Audio over Cat5/Cat6 Extender Kit, Wallplate Transmitter and Receiver, Up to 700 ft. (213 m)

MODEL NUMBER: **B136-101-WP-1**



Is your TV or other display far away from your audio/video source? This wallplate kit allows a TV, projector, etc. with component video input to be placed up to 300 ft. away from a component audio/video source using ordinary Cat5e UTP cabling. It's great for presentation/conference rooms at a great price!

### Description

Tripp Lite's B136-101-WP-1 Cat5 Extender Wallplate Kit with Component Video + Stereo Audio comes with both local and remote wallplates, allowing you to place a TV, Projector, etc up to 300-ft. (91.44 m) away from the source. A 1080i (60Hz) Component Video and Stereo Audio signal can be extended up to 300-ft. (91.44 m) when using 24Awg, Solid Wire UTP cable (Tripp Lite N022-01K-GY or N222-01K-GY); or up to 400-ft. (121.92 m) when using Zero-Skew UTP cable (Tripp Lite P524-01K). A 480p (60Hz) Component Video and Stereo Audio signal can be extended up to 500-ft. (152.4 m) when using 24Awg, Solid Wire UTP cable (Tripp Lite N022-01K-GY or N222-01K-GY); or up to 700-ft. (213.36 m) when using Zero-Skew UTP cable (Tripp Lite P524-01K). Simple RJ45 Jack connection on the back of the wallplates. No external power required.

### Features

- Comes with both local and remote wallplates
- Easy RJ45 rear connection jacks on both wallplates
- A 1080i (60Hz) Component Video and Stereo Audio signal can be extended up to 300-ft. (91.44 m) when using 24Awg, Solid Wire UTP cable (Tripp Lite N022-01K-GY or N222-01K-GY); or, up to 400-ft. (121.92 m) when using Zero-Skew UTP cable (Tripp Lite P524-01K)
- No external power required

## Specifications

| OVERVIEW     |              |
|--------------|--------------|
| UPC Code     | 037332162878 |
| Product Type | Extender Kit |

### Highlights

- Extends a 1080i (60Hz) Component Video and Stereo Audio signal up to 300-ft. (91.44 m)
- No external power required

### Package Includes

- B136-101-WP-1 Cat5 Extender Wallplate Kit with Component Video + Stereo Audio ( 2 pieces )
- Wallplate Mounting Screws
- Owner's Manual



|                                       |  |
|---------------------------------------|--|
| Technology                            | Component; Stereo Audio; Cat5/5e; Cat6 |
| <b>VIDEO</b>                          |  |
| Max Supported Video Resolution        | 1920x1080 (1080i @ 60Hz)               |
| Max 720P Range (ft)                   | 400                                    |
| Max 1280 x 720 (720p) Range (ft)      | 328                                    |
| Transmitter Video Input               | Component (RCA)                        |
| Transmitter - Number of Video Outputs | 1                                      |
| Receiver/Transceiver Video Output     | Component (RCA)                        |
| Receiver - Number of Video Outputs    | 1                                      |
| Recommended Cabling                   | P524-01K                               |
| HDR Support                           | No                                     |
| 3D Video Supported                    | Yes                                    |
| Maximum Signal Range (ft)             | 700                                    |
| Maximum Signal Range (m)              | 213                                    |
| <b>AUDIO</b>                          |  |
| Audio Input                           | RCA (x2) Stereo                        |
| Audio Output                          | RCA (x2) Stereo                        |
| Audio Specification                   | Stereo Audio                           |
| <b>INPUT</b>                          |  |
| Bus Powered                           | No                                     |
| <b>POWER</b>                          |  |
| Power Over Cable (PoC) Support        | No                                     |
| <b>PHYSICAL</b>                       |  |
| Color                                 | White                                  |
| Number of Displays                    | 1                                      |
| Form Factor/Mounting Options          | Wallplate                              |
| Receiver Unit Dimensions (hwd / in.)  | 4.53 x 2.76 x 2                        |
| Receiver Unit Weight (lbs.)           | 0.5                                    |
| Shipping Dimensions (hwd / cm)        | 4.32 x 20.07 x 13.97                   |
| Shipping Dimensions (hwd / in.)       | 1.70 x 7.90 x 5.50                     |
| Shipping Weight (kg)                  | 0.32                                   |
| Shipping Weight (lbs.)                | 0.70                                   |



|  |                           |
|--|---------------------------|
| Transmitter Unit Dimensions (hwd / in.)      | 4.53 x 2.76 x 2           |
| Transmitter Unit Weight (lbs.)               | 0.5                       |
| Unit Packaging Type                          | Box                       |
| Housing                                      | Plastic                   |
| <b>ENVIRONMENTAL</b>                         |                           |
| Operating Temperature Range                  | 32 to 104°F (0 to 40°C)   |
| Storage Temperature Range                    | 14 to 158 F (-10 to 70 C) |
| Relative Humidity                            | 0% to 85%, Non-Condensing |
| <b>COMMUNICATIONS</b>                        |                           |
| Max 1024 x 768 Range (ft)                    | 700                       |
| Max 480P Range (ft)                          | 700                       |
| Max 1440 x 900 Range (ft)                    | 400                       |
| Max 1080i Range (ft)                         | 400                       |
| Max 480i Range (ft)                          | 700                       |
| Max 640 x 480 Range (ft)                     | 700                       |
| Max 800 x 600 Range (ft)                     | 700                       |
| Max 1600 x 1200 Range (ft)                   | 400                       |
| EDID Compatible                              | No                        |
| IR Remote Extension Support                  | No                        |
| RS-232 Serial Extension Support              | No                        |
| Consumer Electronics Control (CEC) Supported | No                        |
| USB Extension Support                        | No                        |
| <b>CONNECTIONS</b>                           |                           |
| Number of Ports                              | 1                         |
| Side A - Connector 1                         | (5) RCA (FEMALE)          |
| Side A - Connector 2                         | RJ45 (FEMALE)             |
| Side B - Connector 1                         | (5) RCA (FEMALE)          |
| Side B - Connector 2                         | RJ45 (FEMALE)             |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                           |
| Driver Required                              | No                        |
| 10/100 Ethernet Extension Support            | No                        |
| Built-In Equalizer                           | No                        |



| <b>STANDARDS &amp; COMPLIANCE</b>   |                                     |
|-------------------------------------|-------------------------------------|
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA) |
| <b>WARRANTY</b>                     |                                     |
| Product Warranty Period (Worldwide) | 1-year limited warranty             |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>