

# USB 3.2 Gen 2 Active Extension Cable - USB-C to USB-A (M/F), 10 Gbps, Data Only, 5 m (16.4 ft.)

# MODEL NUMBER: U330-05M-C2A-G2











Active 16 ft. extension cord increases the distance between two USB devices, including MacBooks and Windows laptops, without signal loss.

#### **Features**

#### USB Extension Cable Connects Computers, Printers, Modems and Other USB Equipment

This USB-C to USB-A Active Extension Cable (M/F) attaches to your current USB 3.2 Gen 2 cable to extend it by five meters (16.4 feet). It connects your MacBook Pro, Windows laptop, Chromebook or other compatible USB-C device to a USB-A webcam, keyboard, printer, portable hard drive, patch panel or other peripheral. The extra length allows you greater flexibility in placing equipment where most needed.

### **Built-In Signal Booster for Peak Performance**

Just connect the active cable's USB-C plug to your computer's USB-C port and the USB-A female connector to a USB device cable to extend your total connection beyond USB's natural five-meter limit. The bus-powered signal booster ensures USB 3.2 Gen 2 data transfer speeds up to 10 Gbps, twice as fast as USB 3.2 Gen 1, with no signal loss. The cable is backward compatible with previous USB generations, so you can use it with legacy equipment.

#### 900mA of Proper Power to Keep Devices Functioning

The U330-05M-C2A-G2 works with standard USB 3.2 Gen 2 cables and provides up to 900mA of power to a connected device.

# **Specifications**

| OVERVIEW       |              |  |
|----------------|--------------|--|
| UPC Code       | 037332268686 |  |
| Technology     | USB 3.x; USB |  |
| USB Cable Type | Active       |  |
|                |              |  |
| INPUT          |              |  |

# **Highlights**

- Adds 5 meters to your existing USB connection to provide flexibility in placing devices
- Connects existing USB-A peripherals to newer laptops or tablets with USB-C ports
- Supports USB 3.2 Gen 2 speeds up to 10 Gbps to ensure fast data transfers
- Provides up to 900mA of power to connected device without need for external power
- Plug-and-play operation with no software required for easy, immediate installation

# **System Requirements**

USB 3.2 Gen 2 computer port and USB 3.2 Gen 2 connected device required to meet USB 3.2 Gen 2 speeds

# **Package Includes**

U330-05M-C2A-G2 USB-C Active Extension Cable, USB-C to USB-A (M/F), 5 m (16.4 ft.)





| Bus Powered                              | Yes                                 |  |
|--|-------------------------------------|--|
| bus rowered                              | Tes                                 |  |
| POWER                                    |                                     |  |
| USB Power Delivery (PD) Charging Support | No                                  |  |
| PHYSICAL                                 |                                     |  |
| Material of Construction                 | TPE + ABS                           |  |
| Color                                    | Black                               |  |
| Cable Jacket Color                       | Black                               |  |
| Cable Jacket Material                    | TPE                                 |  |
| Cable Outer Diameter (OD)                | 4.8MM                               |  |
| Cable Length (ft.)                       | 16.4                                |  |
| Cable Length (m)                         | 5.00                                |  |
| Unit Packaging Type                      | Polybag                             |  |
| Unit Weight (lbs.)                       | 0.51                                |  |
| Unit Weight (kg)                         | 0.23                                |  |
| ENVIRONMENTAL                            |                                     |  |
| Operating Temperature Range              | 32 to 113F (0 to 45C)               |  |
| Storage Temperature Range                | 14 to 158F (-10 to 70C)             |  |
| Operating Humidity Range                 | 10% TO 85% RH, Non-Condensing       |  |
| Storage Humidity Range                   | 5% TO 90% RH, Non-Condensing        |  |
| Power Provided to Connected Device(s)    | 900mA                               |  |
| CONNECTIONS                              |                                     |  |
| Side A - Connector 1                     | USB C (MALE)                        |  |
| Side B - Connector 1                     | USB A (FEMALE)                      |  |
| Connector Plating                        | Nickel                              |  |
| Contact Plating                          | Gold; Nickel                        |  |
| FEATURES & SPECIFICATIONS                |                                     |  |
| USB Specification                        | USB 3.2 Gen 2 (Up to 10 Gbps)       |  |
| Driver Required                          | No                                  |  |
| STANDARDS & COMPLIANCE                   |                                     |  |
| Product Compliance                       | RoHS; CE (Europe); REACH; FCC (USA) |  |



**Tripp Lite**1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

| WARRANTY                               |                         |
|--|-------------------------|
| Product Warranty Period<br>(Worldwide) | 3-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>