

## USB-C to VGA Adapter with USB-A Port and PD Charging, White

MODEL NUMBER: **U444-06N-VU-C**



Adds VGA, USB-A and USB-C PD ports to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC.

### Description

The U444-06N-VU-C USB 3.1 Gen 1 USB-C to VGA Adapter expands the potential of your tablet, laptop, Chromebook, MacBook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for transmitting 1080p video to a large display, adding a thumb drive or other USB peripheral, and powering and charging a PD Charging-compliant mobile device—all at the same time.

With a source device that also supports USB DisplayPort Alternate Mode, you can extend video from your primary display to another, duplicate the same video on both displays or change the second display to your primary.

The plug-and-play U444-06N-VU-C requires no software, drivers or external power. Connect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

To send HD video to a VGA television, projector or monitor, connect the VGA port to the display using a VGA cable (sold separately). The VGA port supports HD video resolutions up to 1920 x 1080 (1080p) at 60 Hz.

The USB-A port accepts USB peripherals, such as a flash drive, mouse, keyboard or printer. It supports fast USB 3.1 Gen 1 data transfer rates up to 5 Gbps and is backward compatible with previous USB generations. The port provides up to 5V/1.5A (7.5W) for fast charging of mobile devices.

Along with data transfer, the USB-C Power Delivery (PD) port provides power and charging to the PD Charging-compliant device (such as a MacBook or Chromebook) the U444-06N-VU-C is connected to. Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 20V 3A (60W).

### Features

#### Turn Your Device's USB-C Port into a Multiport Workstation

- Ideal for transmitting video to a large display, adding a USB peripheral, and powering and charging a PD Charging-compliant mobile device simultaneously
- Plug-and-play operation with no software, drivers or external power required
- About the size of a credit card for easy carrying in a pocket, purse or laptop bag

#### Transmit Crystal-Clear 1080p Video to VGA Display

- Compatible with USB-C or Thunderbolt 3 source devices that support USB DisplayPort Alternate Mode
- Supports HD video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Extends video from your primary display to another

### Highlights

- Supports USB DisplayPort Alternate Mode for transmitting video
- Supports HD video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- USB-C port supports both data transfer and USB Power Delivery (PD) charging with power input up to 20V 3A (60W)
- Reversible USB-C plug connects in either direction
- USB-A port provides up to 5V/1.5A (7.5W) of fast-charging power.
- Plug-and-play operation with no software or drivers required

### System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with VGA input (VGA port)

### Package Includes

- U444-06N-VU-C USB 3.1 Gen 1 USB-C to VGA Adapter
- Owner's manual



- Duplicates the same video on 2 displays
- Converts a secondary display to your primary display

**Connect a USB Peripheral**

- USB-A port accepts flash drives, mice, keyboards, printers and other USB peripherals
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.1
- Provides up to 5V/1.5A (7.5W) of fast-charging power.

Note: Host must support USB OTG (On-the-Go)

**Charge a Connected Device**

- USB-C PD port connects to wall charger to power and charge the connected PD Charging-compliant USB-C/Thunderbolt 3 device
- Supports power input up to 20V 3A (60W)
- USB-C port also supports data transfer

Note: USB-C PD port does not support Quick Charge (QC).

**Built-In Cable with Reversible USB-C Connector**

- Fumble-free reversible USB-C plug connects in either direction for quick connection every time

## Specifications

| OVERVIEW                                 |                                 |
|--|---------------------------------|
| UPC Code                                 | 037332193711                    |
| Technology                               | VGA/SVGA                        |
| Host Connector                           | USB C (MALE)                    |
| VIDEO                                    |                                 |
| Max Supported Video Resolution           | VGA: 1920 X 1080 (1080P) @ 60HZ |
| INPUT                                    |                                 |
| Bus Powered                              | Yes                             |
| Product Length (in.)                     | 6                               |
| Product Length (cm.)                     | 15.24                           |
| Product Length (ft.)                     | 0.5                             |
| Product Length (m.)                      | 0.15                            |
| BATTERY                                  |                                 |
| Battery Charging (5V/1.5A Port)          | Yes                             |
| POWER                                    |                                 |
| Power Consumption (Watts)                | 1.8                             |
| USB Power Delivery (PD) Charging Support | Yes                             |



|  |   |
|--|---|
| USB Power Delivery (PD) Charging Specification | 2.0   |
| External Power Supply                          | Yes   |
| <b>CHARGING</b>                                |   |
| Total Charging Watts                           | 60  |
| Charging Ports / Amps                          | 1.5A; 3A  |
| <b>PHYSICAL</b>                                |   |
| Material of Construction                       | PVC, ABS  |
| Color  | White   |
| Cable Jacket Rating                            | VW-1  |
| Shipping Dimensions (hwd / in.)                | 0.90 x 3.90 x 5.60  |
| Shipping Weight (lbs.)                         | 0.19  |
| Unit Dimensions (hwd / in.)                    | 0.57 x 3.1 x 1.6  |
| Unit Packaging Type                            | Box   |
| Unit Weight (lbs.)                             | 0.09  |
| Unit Weight (kg)                               | 0.04  |
| <b>ENVIRONMENTAL</b>                           |   |
| Operating Temperature Range                    | 32 to 113 F (0 to 45 C)   |
| Storage Temperature Range                      | 14 to 158 F (-10 to 70 C)                                       |
| BTUs   | 6.1 BTU/Hr  |
| Operating Humidity Range                       | 10% to 85% RH, Non-Condensing                                   |
| Storage Humidity Range                         | 5% to 90% RH, Non-Condensing                                    |
| Power Provided to Connected Device(s)          | 5V 0.9A (4.5W) Output (USB-A), Up to 20V 3A (60W) Input (USB-C) |
| <b>CONNECTIONS</b>                             |   |
| Number of Ports                                | 3   |
| Side A - Connector 1                           | USB C (MALE)  |
| Side B - Connector 1                           | HD15 (FEMALE)   |
| Side B - Connector 2                           | USB 3.0 A (FEMALE)  |
| Side B - Connector 3                           | USB C (FEMALE)  |
| Connector Plating                              | Nickel  |
| <b>FEATURES &amp; SPECIFICATIONS</b>           |   |
| USB Specification                              | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)            |



|                                     |                                     |
|-------------------------------------|-------------------------------------|
| Driver Required                     | No                                  |
| UASP Support                        | No                                  |
| Auto MDIX Support                   | No                                  |
| Full Duplex Support                 | No                                  |
| Suspend Mode Support                | No                                  |
| Remote Wakeup Support               | No                                  |
| <b>STANDARDS &amp; COMPLIANCE</b>   |                                     |
| Certification & Compliance          | CE (Europe); RoHS; REACH; FCC (USA) |
| <b>WARRANTY</b>                     |                                     |
| Product Warranty Period (Worldwide) | 3-year limited warranty             |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>